

運動用リング (JIS B 2401-1991・Pシリーズ)

JIS規格品のみ掲載しております
規格外の寸法もございますので詳しくはお問い合わせください

呼び寸法	内径	公差	線径	公差
P-3	2.8	±0.14	1.9	±0.08
P-4	3.8	±0.14		
P-5	4.8	±0.15		
P-6	5.8	±0.15		
P-7	6.8	±0.16		
P-8	7.8	±0.16		
P-9	8.8	±0.17		
P-10	9.8	±0.17		
P-10A	9.8	±0.17		
P-11	10.8	±0.18		
P-11.2	11.0	±0.18		
P-12	11.8	±0.19		
P-12.5	12.3	±0.19		
P-14	13.8	±0.19		
P-15	14.8	±0.20		
P-16	15.8	±0.20		
P-18	17.8	±0.21		
P-20	19.8	±0.22		
P-21	20.8	±0.23		
P-22	21.8	±0.24		
			2.4	±0.09

呼び寸法	内径	公差	線径	公差
P-22A	21.7	±0.24	3.5	±0.10
P-22.4	22.1	±0.24		
P-24	23.7	±0.24		
P-25	24.7	±0.25		
P-25.5	25.2	±0.25		
P-26	25.7	±0.26		
P-28	27.7	±0.25		
P-29	28.7	±0.29		
P-29.5	29.2	±0.29		
P-30	29.7	±0.29		
P-31	30.7	±0.30		
P-31.5	31.2	±0.31		
P-32	31.7	±0.31		
P-34	33.7	±0.33		
P-35	34.7	±0.34		
P-35.5	35.2	±0.34		
P-36	35.7	±0.34		
P-38	37.7	±0.37		
P-39	38.7	±0.37		
P-40	39.7	±0.37		
P-41	40.7	±0.38		
P-42	41.7	±0.39		
P-44	43.7	±0.41		
P-45	44.7	±0.41		
P-46	45.7	±0.42		
P-48	47.7	±0.44		
P-49	48.7	±0.45		
P-50	49.7	±0.45		

株式会社 ヤマキン

大阪府大阪市東成区大今里西1-19-9

TEL 06-6971-1215

FAX 06-3972-8625

e-mail : info@yamakinweb.com

HP : <https://www.yamakinweb.com>

呼び寸法	内径	公差	線径	公差
P-48A	47.6	±0.44	5.7	±0.13
P-50A	49.6	±0.45		
P-52	51.6	±0.47		
P-53	52.6	±0.48		
P-55	54.6	±0.49		
P-56	55.6	±0.50		
P-58	57.6	±0.52		
P-60	59.6	±0.53		
P-62	61.6	±0.55		
P-63	62.6	±0.56		
P-65	64.6	±0.57		
P-67	66.6	±0.59		
P-70	69.6	±0.61		
P-71	70.6	±0.62		
P-75	74.6	±0.65		
P-80	79.6	±0.69		
P-85	84.6	±0.73		
P-90	89.6	±0.77		
P-95	94.6	±0.81		
P-100	99.6	±0.84		
P-102	101.6	±0.85		
P-105	104.6	±0.87		
P-110	109.6	±0.91		
P-112	111.6	±0.92		
P-115	114.6	±0.94		
P-120	119.6	±0.98		
P-125	124.6	±1.01		
P-130	129.6	±1.05		
P-132	131.6	±1.06		
P-135	134.6	±1.09		
P-140	139.6	±1.12		
P-145	144.6	±1.16		
P-150	149.6	±1.19		

呼び寸法	内径	公差	線径	公差
P-150A	149.5	±1.19	8.4	±0.15
P-155	154.5	±1.23		
P-160	159.5	±1.26		
P-165	164.5	±1.30		
P-170	169.5	±1.33		
P-175	174.5	±1.37		
P-180	179.5	±1.40		
P-185	184.5	±1.44		
P-190	189.5	±1.48		
P-195	194.5	±1.51		
P-200	199.5	±1.55		
P-205	204.5	±1.58		
P-209	208.5	±1.61		
P-210	209.5	±1.62		
P-215	214.5	±1.65		
P-220	219.5	±1.68		
P-225	224.5	±1.71		
P-230	229.5	±1.75		
P-235	234.5	±1.78		
P-240	239.5	±1.81		
P-245	244.5	±1.84		
P-250	249.5	±1.88		
P-255	254.5	±1.91		
P-260	259.5	±1.94		
P-265	264.5	±1.97		
P-270	269.5	±2.01		
P-275	274.5	±2.04		
P-280	279.5	±2.07		
P-285	284.5	±2.10		
P-290	289.5	±2.14		
P-295	294.5	±2.17		
P-300	299.5	±2.20		
P-315	314.5	±2.30		
P-320	319.5	±2.33		
P-335	334.5	±2.42		
P-340	339.5	±2.45		
P-355	354.5	±2.54		
P-360	359.5	±2.57		
P-375	374.5	±2.67		
P-385	384.5	±2.73		
P-400	399.5	±2.82		

株式会社 ヤマキン

大阪府大阪市東成区大今里西1-19-9

TEL 06-6971-1215

FAX 06-3972-8625

e-mail : info@yamakinweb.com

HP : https://www.yamakinweb.com