

内径順 JIS オリング一覧

JIS規格品のみ掲載しております  
規格外の寸法もございますので詳しくはお問い合わせください

呼び寸法	内径	線径	計算上外径
P-3	2.8	1.9	6.6
P-4	3.8	1.9	7.6
P-5	4.8	1.9	8.6
P-6	5.8	1.9	9.6
P-7	6.8	1.9	10.6
P-8	7.8	1.9	11.6
P-9	8.8	1.9	12.6
P-10	9.8	1.9	13.6
P-10A	9.8	2.4	14.6
P-11	10.8	2.4	15.6
P-11.2	11.0	2.4	15.8
P-12	11.8	2.4	16.6
P-12.5	12.3	2.4	17.1
P-14	13.8	2.4	18.6
V-15	14.5	4.0	22.5
P-15	14.8	2.4	19.6
P-16	15.8	2.4	20.6
P-18	17.8	2.4	22.6
P-20	19.8	2.4	24.6
P-21	20.8	2.4	25.6
P-31.5	21.2	3.5	28.2
P-22A	21.7	3.5	28.7
P-22	21.8	2.4	26.6
P-22.4	22.1	3.5	29.1
V-24	23.5	4.0	31.5
P-24	23.7	3.5	30.7
G-25	24.4	3.1	30.6
P-25	24.7	3.5	31.7
P-25.5	25.2	3.5	32.2
P-26	25.7	3.5	32.7
P-28	27.7	3.5	34.7
P-29	28.7	3.5	35.7
P-29.5	29.2	3.5	36.2
G-30	29.4	3.1	35.6
P-30	29.7	3.5	36.7
P-31	30.7	3.5	37.7
P-32	31.7	3.5	38.7
V-34	33.5	4.0	41.5
P-34	33.7	3.5	40.7
G-35	34.4	3.1	40.6
P-35	34.7	3.5	41.7
P-35.5	35.2	3.5	42.2
P-36	35.7	3.5	42.7
P-38	37.7	3.5	44.7
P-39	38.7	3.5	45.7
G-40	39.4	3.1	45.6
V-40	39.5	4.0	47.5
P-40	39.7	3.5	46.7
P-41	40.7	3.5	47.7
P-42	41.7	3.5	48.7
P-44	43.7	3.5	50.7
G-45	44.4	3.1	50.6
P-45	44.7	3.5	51.7

呼び寸法	内径	線径	計算上外径
P-46	45.7	3.5	52.7
P-48A	47.6	5.7	59.0
P-48	47.7	3.5	54.7
P-49	48.7	3.5	55.7
G-50	49.4	3.1	55.6
P-50A	49.6	5.7	61.0
P-50	49.7	3.5	56.7
P-52	51.6	5.7	63.0
P-53	52.6	5.7	64.0
G-55	54.4	3.1	60.6
V-55	54.5	4.0	62.5
P-55	54.6	5.7	66.0
P-56	55.6	5.7	67.0
P-58	57.6	5.7	69.0
G-60	59.4	3.1	65.6
P-60	59.6	5.7	71.0
P-62	61.6	5.7	73.0
P-63	62.6	5.7	74.0
G-65	64.4	3.1	70.6
P-65	64.6	5.7	76.0
P-67	66.6	5.7	78.0
V-70	69.0	4.0	77.0
G-70	69.4	3.1	75.6
P-70	69.6	5.7	81.0
P-71	70.6	5.7	82.0
G-75	74.4	3.1	80.6
P-75	74.6	5.7	86.0
G-80	79.4	3.1	85.6
P-80	79.6	5.7	91.0
V-85	84.0	4.0	92.0
G-85	84.4	3.1	90.6
P-85	84.6	5.7	96.0
G-90	89.4	3.1	95.6
P-90	89.6	5.7	101.0
G-95	94.4	3.1	100.6
P-95	94.6	5.7	106.0
V-100	99.0	4.0	107.0
G-100	99.4	3.1	105.6
P-100	99.6	5.7	111.0
P-102	101.6	5.7	113.0
G-105	104.4	3.1	110.6
P-105	104.6	5.7	116.0
G-110	109.4	3.1	115.6

株式会社 ヤマキン

大阪府大阪市東成区大今里西1-19-9

TEL 06-6971-1215

FAX 06-3972-8625

e-mail : info@yamakinweb.com

HP : <https://www.yamakinweb.com>

呼び寸法	内径	線径	計算上外径
P-110	109.6	5.7	121.0
P-112	111.6	5.7	123.0
G-115	114.4	3.1	120.6
P-115	114.6	5.7	126.0
V-120	119.0	4.0	127.0
G-120	119.4	3.1	125.6
P-120	119.6	5.7	131.0
G-125	124.4	3.1	130.6
P-125	124.6	5.7	136.0
G-130	129.4	3.1	135.6
P-130	129.6	5.7	141.0
P-132	131.6	5.7	143.0
G-135	134.4	3.1	140.6
P-135	134.6	5.7	146.0
G-140	139.4	3.1	145.6
P-140	139.6	5.7	151.0
G-145	144.4	3.1	150.6
P-145	144.6	5.7	156.0
V-150	148.5	4.0	156.5
G-150	149.3	5.7	160.7
P-150A	149.5	8.4	166.3
P-150	149.6	5.7	161.0
G-155	154.3	5.7	165.7
P-155	154.5	8.4	171.3
G-160	159.3	5.7	170.7
P-160	159.5	8.4	176.3
G-165	164.3	5.7	175.7
P-165	164.5	8.4	181.3
G-170	169.3	5.7	180.7
P-170	169.5	8.4	186.3
V-175	173.0	4.0	181.0
G-175	174.3	5.7	185.7
P-175	174.5	8.4	191.3
G-180	179.3	5.7	190.7
P-180	179.5	8.4	196.3
G-185	184.3	5.7	195.7
P-185	184.5	8.4	201.3
G-190	189.3	5.7	200.7
P-190	189.5	8.4	206.3
G-195	194.3	5.7	205.7
P-195	194.5	8.4	211.3
G-200	199.3	5.7	210.7
P-200	199.5	8.4	216.3
P-205	204.5	8.4	221.3
P-209	208.5	8.4	225.3
G-210	209.3	5.7	220.7
P-210	209.5	8.4	226.3
P-215	214.5	8.4	231.3
G-220	219.3	5.7	230.7
P-220	219.5	8.4	236.3
V-225	222.5	6.0	234.5
P-225	224.5	8.4	241.3
G-230	229.3	5.7	240.7
P-230	229.5	8.4	246.3

呼び寸法	内径	線径	計算上外径
P-235	234.5	8.4	251.3
G-240	239.3	5.7	250.7
P-240	239.5	8.4	256.3
P-245	244.5	8.4	261.3
G-250	249.3	5.7	260.7
P-250	249.5	8.4	266.3
P-255	254.5	8.4	271.3
G-260	259.3	5.7	270.7
P-260	259.5	8.4	276.3
P-265	264.5	8.4	281.3
G-270	269.3	5.7	280.7
P-270	269.5	8.4	286.3
V-275	272.0	6.0	284.0
P-275	274.5	8.4	291.3
G-280	279.3	5.7	290.7
P-280	279.5	8.4	296.3
P-285	284.5	8.4	301.3
G-290	289.3	5.7	300.7
P-290	289.5	8.4	306.3
P-295	294.5	8.4	311.3
G-300	299.3	5.7	310.7
P-300	299.5	8.4	316.3
P-315	314.5	8.4	331.3
P-320	319.5	8.4	336.3
V-325	321.5	6.0	333.5
P-335	334.5	8.4	351.3
P-340	339.5	8.4	356.3
P-355	354.5	8.4	371.3
P-360	359.5	8.4	376.3
P-375	374.5	8.4	391.3
V-380	376.0	6.0	388.0
P-385	384.5	8.4	401.3
P-400	399.5	8.4	416.3
V-430	425.5	6.0	437.5
V-480	475.0	10.0	495.0
V-530	524.5	10.0	544.5
V-585	579.0	10.0	599.0
V-640	633.5	10.0	653.5
V-690	683.0	10.0	703.0
V-740	732.5	10.0	752.5
V-790	782.0	10.0	802.0
V-845	836.5	10.0	856.5
V-950	940.5	10.0	960.5
V-1055	1044.0	10.0	1064.0

株式会社 ヤマキン

大阪府大阪市東成区大今里西1-19-9

TEL 06-6971-1215

FAX 06-3972-8625

e-mail : info@yamakinweb.com

HP : <https://www.yamakinweb.com>