

外径順 JIS オリング一覧

JIS規格品のみ掲載しております

規格外の寸法もございますので詳しくはお問い合わせください

呼び寸法	計算上外径	内径	線径
P-3	6.6	2.8	1.9
P-4	7.6	3.8	1.9
P-5	8.6	4.8	1.9
P-6	9.6	5.8	1.9
P-7	10.6	6.8	1.9
P-8	11.6	7.8	1.9
P-9	12.6	8.8	1.9
P-10	13.6	9.8	1.9
P-10A	14.6	9.8	2.4
P-11	15.6	10.8	2.4
P-11.2	15.8	11	2.4
P-12	16.6	11.8	2.4
P-12.5	17.1	12.3	2.4
P-14	18.6	13.8	2.4
P-15	19.6	14.8	2.4
P-16	20.6	15.8	2.4
V-15	22.5	14.5	4
P-18	22.6	17.8	2.4
P-20	24.6	19.8	2.4
P-21	25.6	20.8	2.4
P-22	26.6	21.8	2.4
P-31.5	28.2	21.2	3.5
P-22A	28.7	21.7	3.5
P-22.4	29.1	22.1	3.5
G-25	30.6	24.4	3.1
P-24	30.7	23.7	3.5
V-24	31.5	23.5	4
P-25	31.7	24.7	3.5
P-25.5	32.2	25.2	3.5
P-26	32.7	25.7	3.5
P-28	34.7	27.7	3.5
G-30	35.6	29.4	3.1
P-29	35.7	28.7	3.5
P-29.5	36.2	29.2	3.5
P-30	36.7	29.7	3.5
P-31	37.7	30.7	3.5
P-32	38.7	31.7	3.5
G-35	40.6	34.4	3.1
P-34	40.7	33.7	3.5
V-34	41.5	33.5	4
P-35	41.7	34.7	3.5
P-35.5	42.2	35.2	3.5
P-36	42.7	35.7	3.5
P-38	44.7	37.7	3.5
G-40	45.6	39.4	3.1
P-39	45.7	38.7	3.5
P-40	46.7	39.7	3.5
V-40	47.5	39.5	4
P-41	47.7	40.7	3.5
P-42	48.7	41.7	3.5
G-45	50.6	44.4	3.1
P-44	50.7	43.7	3.5
P-45	51.7	44.7	3.5

呼び寸法	計算上外径	内径	線径
P-46	52.7	45.7	3.5
P-48	54.7	47.7	3.5
G-50	55.6	49.4	3.1
P-49	55.7	48.7	3.5
P-50	56.7	49.7	3.5
P-48A	59	47.6	5.7
G-55	60.6	54.4	3.1
P-50A	61	49.6	5.7
V-55	62.5	54.5	4
P-52	63	51.6	5.7
P-53	64	52.6	5.7
G-60	65.6	59.4	3.1
P-55	66	54.6	5.7
P-56	67	55.6	5.7
P-58	69	57.6	5.7
G-65	70.6	64.4	3.1
P-60	71	59.6	5.7
P-62	73	61.6	5.7
P-63	74	62.6	5.7
G-70	75.6	69.4	3.1
P-65	76	64.6	5.7
V-70	77	69	4
P-67	78	66.6	5.7
G-75	80.6	74.4	3.1
P-70	81	69.6	5.7
P-71	82	70.6	5.7
G-80	85.6	79.4	3.1
P-75	86	74.6	5.7
G-85	90.6	84.4	3.1
P-80	91	79.6	5.7
V-85	92	84	4
G-90	95.6	89.4	3.1
P-85	96	84.6	5.7
G-95	100.6	94.4	3.1
P-90	101	89.6	5.7
G-100	105.6	99.4	3.1
P-95	106	94.6	5.7
V-100	107	99	4
G-105	110.6	104.4	3.1
P-100	111	99.6	5.7
P-102	113	101.6	5.7
G-110	115.6	109.4	3.1
P-105	116	104.6	5.7

株式会社 ヤマキン

大阪府大阪市東成区大今里西1-19-9

TEL 06-6971-1215

FAX 06-3972-8625

e-mail : info@yamakinweb.com

HP : https://www.yamakinweb.com

呼び寸法	計算上外径	内径	線径
G-115	120.6	114.4	3.1
P-110	121	109.6	5.7
P-112	123	111.6	5.7
G-120	125.6	119.4	3.1
P-115	126	114.6	5.7
V-120	127	119	4
G-125	130.6	124.4	3.1
P-120	131	119.6	5.7
G-130	135.6	129.4	3.1
P-125	136	124.6	5.7
G-135	140.6	134.4	3.1
P-130	141	129.6	5.7
P-132	143	131.6	5.7
G-140	145.6	139.4	3.1
P-135	146	134.6	5.7
G-145	150.6	144.4	3.1
P-140	151	139.6	5.7
P-145	156	144.6	5.7
V-150	156.5	148.5	4
G-150	160.7	149.3	5.7
P-150	161	149.6	5.7
G-155	165.7	154.3	5.7
P-150A	166.3	149.5	8.4
G-160	170.7	159.3	5.7
P-155	171.3	154.5	8.4
G-165	175.7	164.3	5.7
P-160	176.3	159.5	8.4
G-170	180.7	169.3	5.7
V-175	181	173	4
P-165	181.3	164.5	8.4
G-175	185.7	174.3	5.7
P-170	186.3	169.5	8.4
G-180	190.7	179.3	5.7
P-175	191.3	174.5	8.4
G-185	195.7	184.3	5.7
P-180	196.3	179.5	8.4
G-190	200.7	189.3	5.7
P-185	201.3	184.5	8.4
G-195	205.7	194.3	5.7
P-190	206.3	189.5	8.4
G-200	210.7	199.3	5.7
P-195	211.3	194.5	8.4
P-200	216.3	199.5	8.4
G-210	220.7	209.3	5.7
P-205	221.3	204.5	8.4
P-209	225.3	208.5	8.4
P-210	226.3	209.5	8.4
G-220	230.7	219.3	5.7
P-215	231.3	214.5	8.4
V-225	234.5	222.5	6
P-220	236.3	219.5	8.4
G-230	240.7	229.3	5.7
P-225	241.3	224.5	8.4
P-230	246.3	229.5	8.4

呼び寸法	計算上外径	内径	線径
G-240	250.7	239.3	5.7
P-235	251.3	234.5	8.4
P-240	256.3	239.5	8.4
G-250	260.7	249.3	5.7
P-245	261.3	244.5	8.4
P-250	266.3	249.5	8.4
G-260	270.7	259.3	5.7
P-255	271.3	254.5	8.4
P-260	276.3	259.5	8.4
G-270	280.7	269.3	5.7
P-265	281.3	264.5	8.4
V-275	284	272	6
P-270	286.3	269.5	8.4
G-280	290.7	279.3	5.7
P-275	291.3	274.5	8.4
P-280	296.3	279.5	8.4
G-290	300.7	289.3	5.7
P-285	301.3	284.5	8.4
P-290	306.3	289.5	8.4
G-300	310.7	299.3	5.7
P-295	311.3	294.5	8.4
P-300	316.3	299.5	8.4
P-315	331.3	314.5	8.4
V-325	333.5	321.5	6
P-320	336.3	319.5	8.4
P-335	351.3	334.5	8.4
P-340	356.3	339.5	8.4
P-355	371.3	354.5	8.4
P-360	376.3	359.5	8.4
V-380	388	376	6
P-375	391.3	374.5	8.4
P-385	401.3	384.5	8.4
P-400	416.3	399.5	8.4
V-430	437.5	425.5	6
V-480	495	475	10
V-530	544.5	524.5	10
V-585	599	579	10
V-640	653.5	633.5	10
V-690	703	683	10
V-740	752.5	732.5	10
V-790	802	782	10
V-845	856.5	836.5	10
V-950	960.5	940.5	10
V-1055	1064	1044	10

株式会社 ヤマキン

大阪府大阪市東成区大今里西1-19-9

TEL 06-6971-1215

FAX 06-3972-8625

e-mail : info@yamakinweb.com

HP : <https://www.yamakinweb.com>