

## 固定用リング (JIS B 2401-1991・Gシリーズ)

JIS規格品のみ掲載しております  
規格外の寸法もございますので詳しくはお問い合わせください

呼び寸法	内径	公差	線径	公差
G-25	24.4	±0.25	3.1	±0.10
G-30	29.4	±0.29		
G-35	34.4	±0.33		
G-40	39.4	±0.37		
G-45	44.4	±0.41		
G-50	49.4	±0.45		
G-55	54.4	±0.49		
G-60	59.4	±0.53		
G-65	64.4	±0.57		
G-70	69.4	±0.61		
G-75	74.4	±0.65		
G-80	79.4	±0.69		
G-85	84.4	±0.73		
G-90	89.4	±0.77		
G-95	94.4	±0.81		
G-100	99.4	±0.85		
G-105	104.4	±0.87		
G-110	109.4	±0.91		
G-115	114.4	±0.94		
G-120	119.4	±0.98		
G-125	124.4	±1.01		
G-130	129.4	±1.05		
G-135	134.4	±1.08		
G-140	139.4	±1.12		
G-145	144.4	±1.16		

呼び寸法	内径	公差	線径	公差
G-150	149.3	±1.19	5.7	±0.13
G-155	154.3	±1.23		
G-160	159.3	±1.26		
G-165	164.3	±1.30		
G-170	169.3	±1.33		
G-175	174.3	±1.37		
G-180	179.3	±1.40		
G-185	184.3	±1.44		
G-190	189.3	±1.47		
G-195	194.3	±1.51		
G-200	199.3	±1.55		
G-210	209.3	±1.61		
G-220	219.3	±1.68		
G-230	229.3	±1.73		
G-240	239.3	±1.81		
G-250	249.3	±1.88		
G-260	259.3	±1.94		
G-270	269.3	±2.01		
G-280	279.3	±1.07		
G-290	289.3	±1.14		
G-300	299.3	±2.20		

株式会社 ヤマキン

大阪府大阪市東成区大今里西1-19-9

TEL 06-6971-1215

FAX 06-3972-8625

e-mail : [info@yamakinweb.com](mailto:info@yamakinweb.com)

HP : <https://www.yamakinweb.com>